

---

**ROOM DETAILS:**

---

NATURE OF ACTIVITIES: Accessible WC  
ROOM SIZE (M<sup>2</sup>): 5  
OCCUPANTS: MAX: Transient MIN: Transient  
OCCUPANCY PERIODS: 8:00AM – 11:00PM  
CEILING TYPE: 600x600 Suspended Ceiling

---

**ENVIRONMENTAL CONDITION:**

---

WINTER: DAY: 19-21 °C db  
NIGHT: 10 °C db  
SUMMER: N/A °C db

---

**DRAINAGE:**

---

FOUL DRAINAGE: Yes  
LABORATORY DRAINAGE: None  
RAINWATER DRAINAGE: None  
OTHER: None

---

**PIPED SUPPLY SYSTEM:**

---

WATER: COLD: Yes DRINKING: None  
HOT: Yes  
APPLIANCES: BASIN: 1no. URINAL: None  
WC: 1no. SHOWER: None  
OTHER: 1no. shower  
COMPRESSED AIR: None  
WET/DRY RISER: None  
SPRINKLERS: None  
OTHER: Thermostatic Mixing Valve (TMV3) set to 41°C

---

**VENTILATION AND NOISE REQUIREMENT:**

---

VENTILATION RATE: 10 ACH  
ROOM PRESSURE: Negative  
NOISE LEVEL: NR30  
SPECIAL REQUIREMENT: Mechanical extract with make up air as required c/w PIR control and 15 minute overrun timer

---

---

**HEATING:**

---

SYSTEM TYPE: Underfloor heating  
SYSTEM CONTROL: Local wall mounted controller

**COOLING:**

---

SYSTEM TYPE: None  
SYSTEM CONTROL: None

**GENERAL AND EMERGENCY LIGHTING:**

---

ILLUMINATION LEVEL: 200 (LUX) GLARE INDEX: 22  
MOUNTING TYPE: Recessed MOUNTING HEIGHT: Ceiling WORKING PLANE: Floor  
LUMINAIRE TYPE: SR2 LAMP TYPE: LED  
CONTROL TYPE: Presence Detection EMERGENCY LIGHTING: To BS 5266-1  
SPECIAL REQUIREMENT: None

**GENERAL LV POWER:**

---

THREE PHASE SUPPLIES: None  
SWITCHED SOCKET OUTLET (SSO): None 230V DOUBLE SWITCHED SOCKET OUTLET (DSSO) None  
UNIVERSAL SERIAL BUS (USB) SOCKET OUTLET: None  
LV SUPPLIES: Extract fan  
Hand dryer  
Disabled Call Alarm (DCA)  
SPECIAL REQUIREMENT: None  
UNINTERRUPTIBLE POWER SUPPLY (UPS): None

**COMMUNICATIONS:**

---

TELEPHONE OUTLET: None TELEVISION/RADIO OUTLET: None  
TWIN DATA OUTLET: None SPECIAL FACILITIES: None

